

MOTUL Tyre Repair 適用表 (AUTO)

	1 本
	2 本
	3 本
	4 本
	5 本

市場に流通しているタイヤ

29th April, 2005

12 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2
35	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2
40	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	2
45	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	2	3
50	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3	3	3
55	1	1	1	1	1	2	2	2	2	2	2	2	3	3	3	3	3
60	1	1	1	1	2	2	2	2	2	2	2	3	3	3	3	3	4
65	1	1	1	2	2	2	2	2	2	2	3	3	3	3	4	4	4
70	1	1	1	2	2	2	2	2	2	3	3	3	3	4	4	4	4
75	1	1	2	2	2	2	2	2	3	3	3	3	4	4	4	4	5
80	1	1	2	2	2	2	2	2	3	3	3	4	4	4	4	5	5
13 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2
35	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2
40	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	2
45	1	1	1	1	1	1	2	2	2	2	2	2	2	2	2	3	3
50	1	1	1	1	2	2	2	2	2	2	2	2	2	3	3	3	3
55	1	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3	3
60	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3	4	4
65	1	1	2	2	2	2	2	2	2	2	3	3	3	3	4	4	4
70	1	1	2	2	2	2	2	2	2	3	3	3	3	4	4	4	5
75	1	2	2	2	2	2	2	2	3	3	3	3	4	4	4	5	5
80	1	2	2	2	2	2	2	2	3	3	3	4	4	4	5	5	5
14 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
35	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2
40	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3
45	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3	3	3
50	1	1	1	1	2	2	2	2	2	2	2	2	2	3	3	3	3
55	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3	3	4
60	1	1	2	2	2	2	2	2	2	2	3	3	3	3	3	4	4
65	1	2	2	2	2	2	2	2	2	3	3	3	3	4	4	4	4
70	1	2	2	2	2	2	2	2	3	3	3	3	4	4	4	4	5
75	1	2	2	2	2	2	2	2	3	3	3	4	4	4	5	5	5
80	1	2	2	2	2	2	2	2	3	3	3	4	4	4	5	5	5

表中のデータは、あくまでも本製品を使用するための指標であり、パンクの状態や諸条件によって必要量は異なります。ご使用の際は、その状況に合わせた使い方をさせていただくことをお勧めします。

## MOTUL Tyre Repair 適用表 (AUTO)

	1 本
	2 本
	3 本
	4 本
	5 本

	市場に流通しているタイヤ
--	--------------

29th April, 2005

15 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2
35	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2
40	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	3	3
45	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3	3	3
50	1	1	1	1	1	2	2	2	2	2	2	2	3	3	3	3	3
55	1	1	1	1	2	2	2	2	2	2	2	3	3	3	3	4	4
60	1	1	1	1	2	2	2	2	2	2	3	3	3	3	4	4	4
65	1	1	1	2	2	2	2	2	2	3	3	3	3	4	4	4	5
70	1	1	2	2	2	2	2	2	3	3	3	3	4	4	4	5	5
75	1	1	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5
80	1	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5
16 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2
35	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2
40	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3	3
45	1	1	1	1	1	1	2	2	2	2	2	2	2	3	3	3	3
50	1	1	1	1	1	2	2	2	2	2	2	2	3	3	3	3	4
55	1	1	1	1	2	2	2	2	2	2	3	3	3	3	3	4	4
60	1	1	1	2	2	2	2	2	2	3	3	3	3	3	4	4	4
65	1	1	1	2	2	2	2	2	3	3	3	3	4	4	4	4	5
70	1	1	2	2	2	2	2	3	3	3	3	4	4	4	4	5	5
75	1	2	2	2	2	2	2	3	3	3	4	4	4	5	5	5	5
80	1	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5
17 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2
35	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3
40	1	1	1	1	1	1	1	2	2	2	2	2	2	2	3	3	3
45	1	1	1	1	1	1	2	2	2	2	2	2	3	3	3	3	3
50	1	1	1	1	1	2	2	2	2	2	2	3	3	3	3	4	4
55	1	1	1	1	2	2	2	2	2	2	3	3	3	3	4	4	4
60	1	1	1	2	2	2	2	2	2	3	3	3	3	4	4	4	4
65	1	1	2	2	2	2	2	2	3	3	3	3	4	4	4	5	5
70	1	1	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5
75	1	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5
80	1	2	2	2	2	2	3	3	3	4	4	4	5	5	5	5	5

表中のデータは、あくまでも本製品を使用するための指標であり、パンクの状態や諸条件によって必要量は異なります。ご使用の際は、その状況に合わせた使い方をさせていただくことをお勧めします。

## MOTUL Tyre Repair 適用表 (AUTO)

	1 本
	2 本
	3 本
	4 本
	5 本

	市場に流通しているタイヤ
--	--------------

29th April, 2005

18 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2
35	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3
40	1	1	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3
45	1	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3	3
50	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3	4	4
55	1	1	2	2	2	2	2	2	2	3	3	3	3	3	4	4	4
60	1	1	2	2	2	2	2	2	3	3	3	3	3	4	4	4	5
65	1	2	2	2	2	2	2	3	3	3	3	4	4	4	4	5	5
70	1	2	2	2	2	2	3	3	3	3	4	4	4	4	5	5	5
75	2	2	2	2	2	3	3	3	3	3	4	4	4	5	5	5	5
80	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5	5
19 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2
35	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	3	3
40	1	1	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3
45	1	1	1	1	2	2	2	2	2	2	2	3	3	3	3	3	4
50	1	1	1	2	2	2	2	2	2	2	3	3	3	3	3	4	4
55	1	1	2	2	2	2	2	2	2	3	3	3	3	4	4	4	4
60	1	2	2	2	2	2	2	2	3	3	3	3	4	4	4	5	5
65	1	2	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5
70	1	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5
75	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5	5
80	2	2	2	2	2	3	3	3	4	4	4	5	5	5	5	5	5
20 inch																	
幅 [mm]	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295
扁平率 [%]																	
30	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2
35	1	1	1	1	1	1	1	2	2	2	2	2	2	2	3	3	3
40	1	1	1	1	2	2	2	2	2	2	2	2	2	3	3	3	3
45	1	1	1	2	2	2	2	2	2	2	2	3	3	3	3	4	4
50	1	1	2	2	2	2	2	2	2	2	3	3	3	3	4	4	4
55	1	2	2	2	2	2	2	2	3	3	3	3	4	4	4	5	5
60	1	2	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5
65	1	2	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5
70	1	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5	5
75	2	2	2	2	3	3	3	3	4	4	4	5	5	5	5	5	5
80	2	2	2	2	3	3	3	4	4	4	5	5	5	5	5	5	5

表中のデータは、あくまでも本製品を使用するための指標であり、パンクの状態や諸条件によって必要量は異なります。ご使用の際は、その状況に合わせた使い方をさせていただくことをお勧めします。

	1 本
	2 本
	3 本
	4 本

市場に流通しているタイヤ

28th April, 2005

10 inch															
幅 [mm] \ 扁平率 [%]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
70	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2
80	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2
90	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
100	1	1	1	1	1	1	1	1	2	2	2	2	2	3	3
11 inch															
幅 [mm] \ 扁平率 [%]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
70	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2
80	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2
90	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
100	1	1	1	1	1	1	1	1	2	2	2	2	2	3	3
12 inch															
幅 [mm] \ 扁平率 [%]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
70	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2
80	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2
90	1	1	1	1	1	1	1	1	1	2	2	2	2	2	3
100	1	1	1	1	1	1	1	1	2	2	2	2	3	3	3
13 inch															
幅 [mm] \ 扁平率 [%]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
70	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2
80	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2
90	1	1	1	1	1	1	1	1	1	2	2	2	2	2	3
100	1	1	1	1	1	1	1	1	2	2	2	2	3	3	3
14 inch															
幅 [mm] \ 扁平率 [%]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
70	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2
80	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
90	1	1	1	1	1	1	1	1	2	2	2	2	2	3	3
100	1	1	1	1	1	1	1	2	2	2	2	2	3	3	3
15 inch															
幅 [mm] \ 扁平率 [%]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
70	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2
80	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
90	1	1	1	1	1	1	1	1	2	2	2	2	2	3	3
100	1	1	1	1	1	1	1	2	2	2	2	3	3	3	4

表中のデータは、あくまでも本製品を使用するための指標であり、パンクの状態や諸条件によって必要量は異なります。ご使用の際は、その状況に合わせた使い方をしていただくことをお勧めします。

	1 本
	2 本
	3 本
	4 本

市場に流通しているタイヤ

28th April, 2005

16 inch															
幅 [mm]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
扁平率 [%]															
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
70	1	1	1	1	1	1	1	1	1	1	1	1	2	2	2
80	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
90	1	1	1	1	1	1	1	1	2	2	2	2	2	3	3
100	1	1	1	1	1	1	1	2	2	2	2	3	3	3	4
17 inch															
幅 [mm]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
扁平率 [%]															
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2
70	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2
80	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2
90	1	1	1	1	1	1	1	1	2	2	2	2	3	3	3
100	1	1	1	1	1	1	2	2	2	2	2	3	3	3	4
18 inch															
幅 [mm]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
扁平率 [%]															
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2
70	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2
80	1	1	1	1	1	1	1	1	1	2	2	2	2	2	3
90	1	1	1	1	1	1	1	2	2	2	2	2	3	3	3
100	1	1	1	1	1	1	2	2	2	2	3	3	3	4	4
19 inch															
幅 [mm]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
扁平率 [%]															
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2
70	1	1	1	1	1	1	1	1	1	1	1	2	2	2	2
80	1	1	1	1	1	1	1	1	1	2	2	2	2	2	3
90	1	1	1	1	1	1	1	2	2	2	2	2	3	3	3
100	1	1	1	1	1	1	2	2	2	2	3	3	3	4	4
20 inch															
幅 [mm]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
扁平率 [%]															
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2
70	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
80	1	1	1	1	1	1	1	1	2	2	2	2	2	3	3
90	1	1	1	1	1	1	1	2	2	2	2	3	3	3	3
100	1	1	1	1	1	1	2	2	2	2	3	3	3	4	4
21 inch															
幅 [mm]	50	70	80	90	100	110	120	130	140	150	160	170	180	190	200
扁平率 [%]															
55	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2
60	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2
70	1	1	1	1	1	1	1	1	1	1	2	2	2	2	2
80	1	1	1	1	1	1	1	1	2	2	2	2	2	3	3
90	1	1	1	1	1	1	1	2	2	2	2	3	3	3	4
100	1	1	1	1	1	2	2	2	2	3	3	3	4	4	4

表中のデータは、あくまでも本製品を使用するための指標であり、パンクの状態や諸条件によって必要量は異なります。ご使用の際は、その状況に合わせた使い方をしていただくことをお勧めします。